



Pass and Seymour Turnlok® 67W76 Watertight Single Receptacle, Yellow Part No. 67W76

Turnlok Watertight Single Receptacle, 20amp 3 480 volt, NEMA Configuration L16-20, Impact resistant Valox lid, cover plate, and receptacle body withstand impacts, chemical, and corrosion.

3-Way

Number of Poles

Features & Benefits

Impact Resistant Valox lid, cover plate, and receptacle body withstand impacts, chemical & corrosion. Stainless steel hinge spring and pin for corrosion resistance.		Spring loaded flip covers provide protection when device is not in use.		
		For Covering Patents, see www.legrand.us/patents.		
Specifications				
General Info				
Product Line	Pass & Seymour	Сс	olor	Yellow
Country Of Origin	United States	St	andard	UL Listed, CSA Listed
Dimensions				
Product Width US	1.85 in	Pr	roduct Depth US	4.03 in
Product Height US	1.85 in			
Listing Agencies / 3r	d Party Agencies			
CSA Listed	Yes			
Technical Informatio	n			
Phase	Three	Nu	umber of Wires	4

Amperage

20 A

Wire Size	14 - 10 AWG	Voltage	480.0 V
Environmental Conditions	Moisture Resistance NEMA 4, 4X, 12, 6, 6P/IP65, 66, 67 (Plug & Connector only) Flammability UL94V0 (boxes & wiring device interiors) Operating Temperature -40°C (without impact) to +60°C continuous UV resistance All exposed material s are UV stabilized		