

Pass and Seymour Flexcor® Support Grips Service and Bus Drop, Single Eye, Cable Diameter 0.41 - 0.56 in. Part No. FC40

FC40: Bus Drop, Closed Mesh, Single Eye, Cable Diameter 0.41 - 0.56 inches, Bale Length 9-in, Mesh Length 5-in, Break Strength 1100 lbs.



## Features & Benefits

| Bus drop grips are used as cable support. They relieve any direct tension fro<br>connection and absorb vibration and flexing. |  | om the critical B  | us drop grips are woven of galvanized steel wir                         |
|---|--|--------------------|---|
| They are offered with eit   | ther the single eye or locking bale attachment.              |                    | port grips are woven of corrosion-resistant<br>ed-stainless steel wire. |
| Most Flexcor products have UL and/or CSA approvals. Please contact factory information.                                       |  | r for approval Bal | e Length: 9: Mesh Length: 5.0   |
| Specifications  |  |                    |   |
| General Info  |  |                    |   |
| Product Line  | Pass & Seymour   | Country Of Origin  | Mexico  |
| Construction  | Support and Strain Relief Grips, Various Types of<br>Pulling | Application Sector | Industrial  |
| Standard  | UL/CSA Approval (consult factory)                            |                    |   |
| Dimensions  |  |                    |   |
| Product Width US  | 0.56 in  | Product Length US  | 5.0 in  |
| Listing Agencies / 3r   | d Party Agencies   |                    |   |
| CSA Listed  | Yes  | CSA File Number    | 67507   |
| Technical Information   | n  |                    |   |
| Maximum Cable Range   | 0.41 in  | Minimum Cable Ran  | ge 0.56 in  |
| Capacity  | Various Cable Diameter Ranges                                | Mounting           | Consult the Factory for Mounting<br>Recommendations                     |
| Load  | Approx. Break Strength: 1100                                 |                    |   |