

radiant Collection

radiant® Tamper-Resistant and Dual Controlled 20A Duplex Self-Test GFCI Receptacles with SafeLock® Protection, 125V, Brown

Part No. 2097TRCI



GFCI receptacles from the radiant® Collection self-test automatically every three seconds to ensure reliable protection from shock due to ground fault occurrences. Meeting National Electrical Code requirements for ground fault protection, GFCI receptacles make it easier to recognize and fix trips right where they happen – no more confusion at the breaker box. 20A outlets are ideal for use with larger appliances and in commercial settings, as well as to meet regional requirements (Chicago, Canada). GFCI protection is required by code in bathrooms, kitchens, garages, basements, outdoor areas, and for any other outlets found within six feet of a sink or water source. GFCI outlets should always be used when replacing existing GFCI outlets during renovation. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately. Spec-Grade devices are engineered to meet federal specifications for use in commercial installations.

Features & Benefits

Protects against shock caused by ground-fault occurrences. Unlike breaker alternatives, GFCI receptacles make it easier to fix trips with a reset button right on the device.

Equipped with proven SafeLock protection feature: if critical components are damaged and protection is lost, power to the outlet is disconnected.

Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an invisible effect.

Features durable, high-impact resistant thermoplastic construction.

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection.

20 Amp feed-thru capacity

Conducts an industry-leading automatic self-test every 3 seconds. If the device ever fails, the indicator light flashes to signal it should be replaced.

Extends GFCI protection to "downstream" outlets when used with feed-thru wiring configuration. Note: Will cut power to face and downstream outlets if wired incorrectly.

Replaces any standard receptacle with ease, in as little as 10 minutes.

More color options available to fit any style, including finishes to match current hardware and lighting trends.

10kA short circuit rating

Specifications

Pass & Seymour	Replaced by Part Number	Replaced by Part Number	
Brown	Finish	Matte	
China	Application Sector	Commercial	
RoHS, CSA, cULus, UL	Туре	GFCI, Outlet, Tamper-Resistant	
1.73 in	Product Depth US	1.03 in	
4.2 in			
Party Agencies			
Yes	cULus ListingNumber	E140596	
	Brown China RoHS, CSA, cULus, UL 1.73 in 4.2 in	Brown Finish China Application Sector RoHS, CSA, cULus, UL Type 1.73 in Product Depth US 4.2 in	

Yes

RoHS Conformant

Technical Information				
Amperage	20 A	Indoor/Outdoor	Indoor	
Environmental Conditions	85% (relative humidity, non-condensing)			