## 

radiant Collection radiant® Tamper-Resistant and Dual Controlled 20A Duplex Self-Test GFCI Receptacles with SafeLock® Protection, 125V, Green Part No. 2097TRCDGN



GFCI receptacles from the radiant® Collection self-test automatically every three seconds to ensure reliable protection from shock due to ground fault occurrences. Meeting National Electrical Code requirements for ground fault protection, GFCI receptacles make it easier to recognize and fix trips right where they happen – no more confusion at the breaker box. 20A outlets are ideal for use with larger appliances and in commercial settings, as well as to meet regional requirements (Chicago, Canada). GFCI protection is required by code in bathrooms, kitchens, garages, basements, outdoor areas, and for any other outlets found within six feet of a sink or water source. GFCI outlets should always be used when replacing existing GFCI outlets during renovation. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately. Spec-Grade devices are engineered to meet federal specifications for use in commercial installations.

## Features & Benefits

Protects against shock caused by ground-fault occurrences. Unlike breaker alternatives, GFCI receptacles make it easier to fix trips with a reset button right or the device.	Conducts an industry-leading automatic self-test every 3 seconds. If the device ever fails, the indicator light flashes to signal it should be replaced.
Equipped with proven SafeLock protection feature: if critical components are damaged and protection is lost, power to the outlet is disconnected.	Extends GFCI protection to "downstream" outlets when used with feed-thru wiring configuration. Note: Will cut power to face and downstream outlets if wired incorrectly.
Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an invisible effect.	Replaces any standard receptacle with ease, in as little as 10 minutes.
Features durable, high-impact resistant thermoplastic construction.	More color options available to fit any style, including finishes to match current hardware and lighting trends.
Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection.	<sup>1</sup> 10kA short circuit rating

20 Amp feed-thru capacity

## Specifications

## General Info

Product Line	Pass & Seymour	Replaced by Part Number	Replaced by Part Number	
Color	Green	Finish	Matte	
Country Of Origin	China	Application Sector	Commercial	
Standard	RoHS, CSA, cULus, UL	Туре	GFCI, Outlet, Tamper-Resistant	
Dimensions				
Product Width US	1.73 in	Product Depth US	1.03 in	

CSA Listed	Yes	cULus ListingNumber	E140596
cULus Listed	Yes	CSA File Number	CSA C22.2 No. 223, CSA C22.2 No. 42
Additional Information			
RoHS Conformant	Yes		

Technical Information					
Amperage	20 A	Indoor/Outdoor	Indoor		
Environmental Conditions	85% (relative humidity, non-condensing)				