



GFCI receptacles from the radiant® Collection self-test automatically every three seconds to ensure reliable protection from shock due to ground fault occurrences. Meeting National Electrical Code requirements for ground fault protection, GFCI receptacles make it easier to recognize and fix trips right where they happen – no more confusion at the breaker box. 20A outlets are ideal for use with larger appliances and in commercial settings, as well as to meet regional requirements (Chicago, Canada). GFCI protection is required by code in bathrooms, kitchens, garages, basements, outdoor areas, and for any other outlets found within six feet of a sink or water source. GFCI outlets should always be used when replacing existing GFCI outlets during renovation. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately. Spec-Grade devices are engineered to meet federal specifications for use in commercial installations.

Features & Benefits

Protects against shock caused by ground-fault occurrences. Unlike breaker Conducts an industry-leading automatic self-test every 3 seconds. If the device alternatives, GFCI receptacles make it easier to fix trips with a reset button right on ever fails, the indicator light flashes to signal it should be replaced. the device. Extends GFCI protection to "downstream" outlets when used with feed-thru wiring Equipped with proven SafeLock protection feature: if critical components are configuration. Note: Will cut power to face and downstream outlets if wired damaged and protection is lost, power to the outlet is disconnected. incorrectly. Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an Replaces any standard receptacle with ease, in as little as 10 minutes. invisible effect. More color options available to fit any style, including finishes to match current Features durable, high-impact resistant thermoplastic construction. hardware and lighting trends. Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with 10kA short circuit rating other designer switches and outlets available from the radiant® Collection.

20 Amp feed-thru capacity

Specifications

General Info

| Product Line | Pass & Seymour | Replaced by Part Number | Replaced by Part Number | |
|------------------------|----------------------|-------------------------|-------------------------------------|--|
| Color | Gray | Finish | Matte | |
| Country Of Origin | China | Application Sector | Commercial | |
| Standard | RoHS, CSA, cULus, UL | Туре | GFCI, Outlet, Tamper-Resistant | |
| Dimensions | | | | |
| Product Width US | 1.73 in | Product Depth US | 1.03 in | |
| Product Height US | 4.2 in | | | |
| Listing Agencies / 3rd | Party Agencies | | | |
| CSA Listed | Yes | cULus ListingNumber | E140596 | |
| cULus Listed | Yes | CSA File Number | CSA C22.2 No. 223, CSA C22.2 No. 42 | |
| Additional Information | | | | |
| RoHS Conformant | Yes | | | |
| | | | | |

| Technical Information | | | | | |
|--------------------------|---|----------------|--------|--|--|
| Amperage | 20 A | Indoor/Outdoor | Indoor | | |
| Environmental Conditions | 85% (relative humidity, non-condensing) | | | | |