

radiant Collection radiant® Tamper-Resistant 20A Simplex Self-Test GFCI Receptacles with SafeLock® Protection, Red Part No. 2097TRSGLRED



Specifically designed for use with large and/or stationary appliances like refrigerators, dishwashers and washing machines, this 20A GFCI outlet provides dedicated power and superior ground-fault protection while also limiting the nuisance tripping often caused by variable motor drives. Like all GFCI electrical outlets and plugs from the radiant® Collection, this device self-tests every three seconds for reliable safety and protection you can trust. Meeting the National Electrical Code requirements for ground fault protection in the home, GFCI wall outlets also make it easier to fix trips right where they happen – no more confusion or running to the breaker box. GFCI protection is required by code in bathrooms, kitchens, garages, basements, outdoor areas, and for any other outlets found within six feet of a sink or water source. GFCI outlets should always be used when replacing existing GFCI outlets during renovation. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately.

Features & Benefits

Protects against shock caused by ground-fault occurrences. Unlike breaker alternatives, GFCI receptacles make it easier to fix trips with a reset button right on the device Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes to signal it should be replaced Career fails, the indicator light flashes flashes for the outlet for the outlet is disconnected Career fails, the indicator flashes flash

Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an invisible effect

More color options available to fit any style, including finishes to match current hardware and lighting trends

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection

Specifications

wired incorrectly

General Info

Product Line	Pass & Seymour	Replaced by Part Number	
Color	Red	Finish	Matte
Country Of Origin	China	Outlet Type	GFCI, Indoor, Residential, Self- Test, Tamper- Resistant
Application Sector	Residential/Commercial	Standard	RoHS, cULus
Warranty Type	1 Year from Day of Sale	Туре	GFCI
Dimensions			
Product Width US	1.73 in	Product Depth US	1.03 in

Product Height US	4.2 in				
Listing Agencies / 3rd Party Agencies					
cULus Listed	Yes				
Additional Information					
RoHS Conformant	Yes	Product Has Potential to Contribute to LEED Yes			
Technical Information					
Is Tamper-Resistant	Yes	Amperage	20 A		
Is Weather Resistant	No	Indoor/Outdoor	Indoor		
Wattage	2500 W	Voltage	125.0 V		