

Pass and Seymour 27W75 Watertight NEMA 4X/6P Locking Connector Part No. 27W75



Locking Watertight Connector, 20amp, 3 250volt, NEMA Configuration L15-20, multipoint sealing system provides environmental protection of NEMA 4, 4X, 6, 6P, and IP67 rated.

## Features & Benefits

| Thermoplastic elastomer (TPV) construction stands up to impacts, oils, chemicals, heat , and weather. | Nickel-Plated blades and contacts for long lasting, superior corrosion resistance. |
|---|--|
| Multipoint sealing system provides environmental protection of NEMA 4, 4X, 6, 6P, & IP67 rated.       | Devices resist high-pressure hose down of 1,500 psi.                               |
| Color coded sealing bushings provided for large range of cord diameters                               | Large ribs on body for a superior grip when mating.                                |

## Specifications

## General Info

| Product Line          | Pass & Seymour | Color             | Yellow                   |
|-----------------------|----------------|-------------------|--------------------------|
| Country Of Origin     | United States  | Standard          | UL Listed, CSA<br>Listed |
| Dimensions            |                |                   |                          |
| Product Width US      | 1.85 in        | Product Length US | 4.03 in                  |
| Technical Information |                |                   |                          |
| Phase                 | Three          | Number of Wires   | 4                        |
| Amperage              | 20 A           | Number of Poles   | 3-Way                    |
| Wire Size             | 14 - 10 AWG    | Voltage           | 250.0 V                  |

| Environmental Conditions |  | Moisture Resistance NEMA 4, 4X, 12, 6, 6P/IP65, |
|--------------------------|--|---|
|                          |  | 66, 67 (Plug & Connector only) Flammability     |
|                          | UL94V0 (boxes & wiring device interiors) Operating |   |
|                          | Temperature -40°C (without impact) to +60°C        |   |
|                          |  | continuous UV resistance All exposed material s |
|                          |  | are UV stabilized                               |
|                          |  |   |