

Pass and Seymour 15A 125V Extra Heavy Duty Spec-Grade Surge Protective Duplex Receptacle, White Part No. 5262WSP



Surge Protective Extra Heavy-Duty Duplex Receptacle offers increased transient protection, reliability and protection notification (with Audible Alarm and LED Indicator). Back and Side Wire, 15A, 125V.

www.legrand.us/patents.

Features & Benefits

Solid-state LED monitor has 25-year minimum life expectancy. A high visibility,
wide-angle lens indicates protection is in place.Corrosion-resistant, plated and tabbed
steel strap locked in to face and back
body to resist pulling away from
face/body assembly.Audible alarm alert of MOV damage. Alarm able to be turned On/Off.Wrap-around steel strap for structural
integrity. Auto-ground is standard, for
easier installation.Impact-resistant thermoplastic exterior resists impacts and scrapes.Triple-wipe, copper-alloy contacts for
superior, more dependable connection.Thermal protection in 3 modes. 3 17mm dual pack MOVs absorb up to 340 Joules of
excess energy in each leg [I - N I - G N-G] with 24,000 amp current handlingFor covering patents, see

excess energy in each leg (L-N, L-G, N-G) with 24,000 amp current handling capability for full, equal and symmetrical protection. Protection response time in less than one nanosecond.

Specifications

General Info

Product Line	Pass & Seymour	Color	White
Finish	Matte	Country Of Origin	Mexico
Application Sector	Commercial	Standard	cUL UL1449, UL498: CSA C22.2 No. 42: ANSI/EEE C62.41 (Formerly IEEE 587), ANSI/IEEE C62.45 Installation Categories "A" (Ring Wave) "B" (Unidirectional Impulse).

Dimensions

Product Width US	1.7 in	Product Depth US	0.875 in	
Product Height US	2.75 in			
Listing Agencies / 3rd Party Agencies				
cULus ListingNumber	140596	cULus Listed	Yes	
Technical Information				
Connection	Back and side wire	Class	IG	
Amperage	15 A	Environmental Conditions	Flammability: UL94 V2	