


adorne Collection adorne® 15A One-Gang Pop-Out Outlet, Magnesium

Part No. ARPTR151GM2



The cleverest way to add power and style, the Pop-Out Outlet extends to offer 3-plug access, then uniquely disappears back into the wall with a simple push when not in use. Made exclusively for use with screwless Wall Plates from the adorne® Collection, sold separately.

Features & Benefits

For complete installation, device must be paired with an adorne® screwless Wall Plate (not included). Available in a range of contemporary colors and stunning finishes.

Perfect anywhere you'd like to hide outlets when not in use, for added style and safety.

Provides additional power with 3-plug access when extended from wall.

Disappears back into the wall with a simple push when not needed.

Installs easily in as little as 15 minutes.

Comes with a special frame for mounting and requires a deep electrical outlet (22.5 cubic inches). No new wires required for typical installation.

Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an invisible effect

More color options available to fit any style, including finishes to match current hardware and lighting trends.

Specifications

General Info Product Line Replaced by Part Number Pass & Seymour Color Finish Frosted Magnesium Country Of Origin China Number of Receptacles Indoor, Pop-Out, Features Pop-Out Outlet Type Residential, Tamper-Resistant **Application Sector** Residential Standard **CULUS** Outlet Warranty Type Limited Lifetime Warranty Туре

Dimensions			
Product Width US	2.99 in	Product Depth US	2.6 in
Product Height US	4.88 in		
Listing Agencies / 3rd F	Party Agencies		
cULus Listed	Yes		
Technical Information			
Phase	Single	Connection	Side and Back Wire
Number of Wires	3	Number of Gangs	1
Amperage	15 A	Number of Poles	Double Pole
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor
NEMA Configuration Code	5-15R	Mounting Type	Вох
Voltage	125.0 V	Connection Type	Internal Pressure Plates
Environmental Conditions	95% (relative humidity, non-condensing)		