

Pass and Seymour 20A 125V Commercial Spec-Grade Duplex Receptacle, Back and Side Wire, Ivory Part No. CRB5362I



Construction Spec Grade Duplex Receptacle Back and Side Wire 20A 125V

Features & Benefits

Corrosion-resistant, plated steel strap locked in to face and back body to resist pulling away from face/body assembly.

Triple-wipe brass contacts ensure lasting, positive contact with plug blades.

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring

Impact-resistant nylon face and thermoplastic back body.

8 hole internal screw-pressure-plate back wire terminals accept #10 - #14 AWG solid or stranded copper or copper-clad conductors.

Terminal compartments isolated from each other for positive conductor containment.

Auto-ground clip assures positive ground.

For covering patents, see www.legrand.us/patents.

For compatible wall plate options, from our screwless plates to our metal wall plates, click here.

Temperature Rise: Maximum 30°C temperature rise at full-rated current TradeMaster unbreakable plates to our radiant after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

Specifications

General Info

Product Line	Pass & Seymour	Color	lvory
Finish	Matte	Country Of Origin	Mexico
Number of Receptacles	2	Outlet Type	Commercial, Indoor
Application Sector	Residential/Commercial	Standard	UL 498
Warranty Type	1-Year Limited Warranty	Туре	Outlet

Dimensions					
Product Width US	1.322 in	Product Depth US	0.78 in		
Product Height US	2.635 in				
Listing Agencies / 3rd Party Agencies					
cULus ListingNumber	140596	cULus Listed	Yes		
Technical Information					
Amperage	20 A	Number of Poles	Double Pole		
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor		
Voltage	125.0 V				