

Pass and Seymour Tamper-Resistant Floor Box Assembly - Two Gang for Wood Sub-Floors, Brass Part No. FB2TRDRKS4B



Tamper-Resistant Floor Box Assembly, Dual-voltage. Two #8 duplex openings, Four threaded screw plugs. Includes 3232 15A, 125A tamper-resistant duplex receptacle, Cat5E Jack, F-connector, Ten Blanks and a low-voltage dider. Brass. For detailed Tamper-Resistant receptacle information, visit our Tamper-Resistant Receptacles page.

Features & Benefits

Tamper-Resistant shutters let plugs in, keep other things out.

Meets UL514(c) and NEC 314.27(c) requirements including scrub water for tile floors.

Large box flange rests on finished floor -- no adjustments needed.

Extra-deep design leaves plenty of wiring room.

Rugged diecast cover plates with durable nickel or brass finish.

Scrub water compliant without caulking, supplied with foam gasket and O-ring-equipped plugs.

Swing brackets mounting, great for tile floors -- eliminates drilling for mounting screws.

Includes 15 Amp, 125 Volt tamper-resistant duplex receptacle, low-voltage divider, Cat 5e jack, F-connector, and blanks.

Specifications

General Info			
Product Line	Pass & Seymour	Color	Brass
Country Of Origin	Mexico	Construction	Wood Floor
Application Sector	Residential/Commercial	Standard	UL Listed
Dimensions			
Cubic Capacity	42.5 cu in		
Listing Agencies / 3rd Party Agencies			
cULus Listed	Yes		

Technical Information Is Tamper-Resistant Yes Number of Outlets 2