



**Wattstopper**  
**Low Voltage (12-32VDC) 0-10V PIR Fixture**  
Part No. FSP-202



FSP-2x2 sensors provide multi-level control based on motion and/or daylight contribution. They control 0-10VDC LED drivers or dimming ballasts, as well as non-dimming ballasts and, with an FSP-Lx Lens, are rated for wet and cold locations. Line and low voltage models are available, and choice of control modes simplifies sensor configuration.

## Features & Benefits

Provides line voltage On/Off switching and 0-10VDC dimming control (FSP-212)

Works with ballasts or LED drivers

High or low trim fully adjustable from 1 to 10V

Time delay from 30 seconds to 30 minutes

Optional cut off delay

Ramp up and fade down times (2 seconds; 10 seconds)

Optional daylighting control

## Specifications

### General Info

Product Line	Wattstopper	UPC Number	754182939626
--------------	-------------	------------	--------------

Country Of Origin	China
-------------------	-------

### Dimensions

Product Width US	2.0 in	Product Weight US	0.11 lb
------------------	--------	-------------------	---------

Product Volume US	8.55 cu in	Product Depth US	1.8 in
-------------------	------------	------------------	--------

Product Height US	1.9 in
-------------------	--------

### Additional Information

RoHS Conformant	Yes	DesignLights Consortium Qualified System	Yes
-----------------	-----	--	-----

Security	Yes
----------	-----

### Technical Information

---

Sensor Type

Daylight, Occupancy

---