

## radiant Collection radiant® Multi-Location Master Dimmer, White

Part No. HCL453PMMW



Allows precise dimming control of a light or fixture. Pair with a Multi-Location Remote Dimmer to control the same fixture from another spot in the room. Part of the radiant® Collection, it also features clean lines and smooth control for a sophisticated touch. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately.

## Features & Benefits

For use with most incandescent, CFL/LED (with the exception of 0 - 10v options) and MLV dimmable bulbs. Installs easily with 3-way wiring for multi-location dimming (use with up to nine remote dimmers).

Low-profile paddle switch offers smoother On/Off control, while a separate, ergonomic slider allows you to adjust light levels with

Constant memory features returns lights to their previous level after a power failure or outage.

Features durable, high-impact resistant thermoplastic construction. finishes to match current hardware and lighting

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection.

Can also be used in single-pole applications for solitary control.

Locator light illuminates when switch is off, emitting a soft glow to help you find it in the dark.

No derating\* required in multi-gang applications. \*Reducing the maximum wattage a dimmer can handle. This is sometimes required for multi-gang applications.

More color options available to fit any style, including finishes to match current hardware and lighting trends.

## Specifications

## General Info

precision.

Product Line	Pass & Seymour	Replaced by Part Number	
Color	White	Country Of Origin	China
Features	Indicator Lights	Switch Type	Paddle

Number of Switches	1	Application Sector	Residential		
Standard	CSA Listed, cULus, UL Listed	Warranty Type	Limited Lifetime Warranty		
Туре	Dimmer				
Dimensions					
Product Width US	2.5 in	Product Depth US	1.25 in		
Product Height US	4.25 in				
Listing Agencies / 3rd Party Agencies					
cULus Listed	Yes				
Technical Information					
Frequency Rating	120VAC 60 Hz	Connection	Screw Terminals		
Number of Gangs	1	Amperage	15 A		
Bulb Compatibility	CFL, Incandescent, LED	Number of Poles	3-Way, Multi-Location, Single Pole		
Wattage	700 W	Mounting Type	Вох		
Voltage	120.0 V	Load	Universal		
Environmental Conditions	Humidity: Less than 95% non condensing				