

radiant Collection radiant® Single Pole/3-Way Switch with Night Light, Black Part No. NTL873BKCC6



Add the convenience of a little extra light, wherever your home needs it, with this combination switch and built-in night light from the radiant® Collection. Easily replacing an existing single-pole or 3way switch, the night light portion has five adjustable light levels and uses a hidden sensor to turn on when it is dark, making it a great addition to bathrooms, kitchens and nurseries. Features the sleek, clean lines of radiant for a sophisticated touch. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately.

Features & Benefits

Replaces any single-pole or 3-way switch with ease, in as little
as 10 minutes. Offers installation flexibility, working in both
single-pole and 3-way applications.Features five adjustable light settings: Ultra Low, Low,
Medium, High and OFF.Hidden sensor controls night light based on ambient light,
automatically turning on when it is dark.Features durable, high-impact resistant thermoplastic
construction.More color options available to fit any style, including finishes
to match current hardware and lighting trends.Complete the look with a sleek, screwless radiant® Wall Plate,
and coordinate with other designer switches and outlets
available from the radiant® Collection.

Specifications

General Info

Pass & Seymour	Replaced by Part Number	
Black	Country Of Origin	China
Nightlight	Switch Type	Push
1	Application Sector	Residential
cULus, UL Listed	Warranty Type	1-Year Limited Warranty
Nightlight		
	Black Nightlight 1 cULus, UL Listed	BlackCountry Of OriginNightlightSwitch Type1Application SectorcULus, UL ListedWarranty Type

Product Height US	4.2 in			
Listing Agencies / 3rd Party Agencies				
cULus ListingNumber	E140597	cULus Listed	Yes	
Technical Information				
Contact Configuration	15A	Operating Cycles	50000	
Contact Rating	120	Number of Gangs	1	
Amperage	15 A	Number of Poles	3-Way, Single Pole	
Mounting Type	Box	Voltage	125.0 V	
Environmental Conditions	UL94 V2			