

Pass and Seymour Extra Heavy Duty Spec. Grade 347VAC Toggle Switches Back and Side Wire, Brown Part No. PS371510

Canadian 1-Pole Switch, Back and Side-Wire, 15A 347V



Features & Benefits

| External screw-pressure-plate back and side wired. Accepts #14 - #10 AWG copper or copper-clad conductors. | Heavy-gauge one-piece copper alloy contact arm virtually eliminates contact bounce. |
|--|---|
| Cam controls fast ''make'' and positive ''break'' to minimize arcing. | Heavy-duty bumper pads for quiet operation. |
| High strength thermoplastic polycarbonate toggle. | Back body made of glass-reinforced nylon. |
| Locking support provides resistance to face and back body separation. | Oversized silver alloy contacts for long life and better heat dissipation. |
| Grounding terminal is standard. | Shallow design for ease of installation. |
| Strap nickel-plated steel with integral ground. | Auto-ground clip assures positive ground. |
| For covering patents, see www.legrand.us/patents. | For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here. |
| arcing. High strength thermoplastic polycarbonate toggle. Locking support provides resistance to face and back body separation. Grounding terminal is standard. Strap nickel-plated steel with integral ground. | Back body made of glass-reinforced nylon. Oversized silver alloy contacts for long life and better heat dissipation. Shallow design for ease of installation. Auto-ground clip assures positive ground. For compatible wall plate options, from our TradeMaster unbreakable plates to |

Specifications

General Info

| Product Line | Pass & Seymour | Color | Brown |
|-------------------|----------------|--------------------|------------------------|
| Country Of Origin | Mexico | Application Sector | Residential/Commercial |
| Standard | UL 20 | | |

Technical Information

| Actuator | Toggle | Contact Rating | 347vac, 15amp |
|-----------------|-------------|----------------|---------------|
| Amperage | 15 A | Action | DPDT |
| Number of Poles | Double Pole | Voltage | 347.0 V |