



## TECHNICAL DATA SHEET

### RIMTEC 4314A NAT RIGID PVC COMPOUND

**DESCRIPTION** - Rimtec 4314A Natural is a high impact compound for extrusion of interior rigid PVC profiles where a low to medium gloss surface finish is required.

#### TYPICAL PROPERTIES

#### ASTM

Specific Gravity ( $\pm .02$ )	1.43	D-792
Hardness (Durometer D/10 $\pm 2$ )	80	D-2240
<u>Using 0.125" Test Specimen</u>		
Izod Impact, ft lbs/in notch	19.0	D-256
Tensile Yield Strength, $10^3$ psi	6.0	D-638
Tensile Modulus, $10^5$ psi	3.7	D-638
Flexural Yield Strength, $10^3$ psi	11.4	D-790
Flexural Modulus, $10^5$ psi	4.5	D-790
DTUL at 264 psi (18.5 kg/cm), ° C		
Unannealed	70	D-648
Annealed	75	D-648

#### FUNCTIONAL CHARACTERISTICS

Rimtec 4314A Natural is designed for interior rigid profile extrusions requiring good impact resistance and excellent surface finish. UL file # E137881 UL 94 Flame V-0 approved.

ASTM CELL CLASSIFICATION	D-1784	16344
--------------------------	--------	-------

**RIMTEC CORPORATION**  
1702 Beverly Road  
Burlington, NJ 08016  
TEL: (609) 387-0011  
FAX: (609) 387-0282

---

These suggestions and data are based on information we believe to be reliable. They are offered in good faith without guarantee or warranty, as conditions and methods of use of our products are beyond our control. We strongly urge that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. User assumes all risks and liabilities in connection with use of this product.