

Pass and Seymour 30A Single Pole Double Throw Switch, Ivory

Part No. 1227I

Single-Pole, Double-Throw Switch, 30A, 120/277V.



Features & Benefits

Oversize silver alloy contacts for

long life and better heat dissipation.

Side wired terminals accept #14 - #10 AWG copper or copper-clad conductors.

Fiber terminal insulation barriers standard.

Can be mounted in standard device boxes or in NEMA 1 sheet steel enclosures.

Bodies, covers, and toggles molded of durable nylon.

Single Pole-Double Throw and Double Pole-Double Throw.

Locking Switches supplied with one 1498-NT key.

Normally open.

For covering patents, see https://www.legrand.us/patents.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, visit www.legrand.us/electrical-wiring-devices/wall-plates.

Specifications

General Info

| Product Line | Pass & Seymour | Color | lvory |
|--------------------|------------------------|---------------------|--------------|
| Finish | Matte | UPC Number | 785007122718 |
| Country Of Origin | Mexico | Features | Durable |
| Switch Type | Toggle | Number of Switches | 1 |
| Application Sector | Commercial, Industrial | Wall Plate Included | No |

| Standard | UL Listed | Warranty Type | 1-Year Limited Warranty | |
|---------------------------------------|---|-----------------------|-------------------------|--|
| Туре | Manual Controller, Tamper-Resistant | | | |
| Dimensions | | | | |
| Product Width US | 1.5 in | Product Depth US | 1.469 in | |
| Product Height US | 3.281 in | | | |
| Listing Agencies / 3rd Party Agencies | | | | |
| CSA Listed | Yes | cULus Listed | Yes | |
| CSA File Number | 17949 | | | |
| Technical Information | | | | |
| Load Rating | 20 A @ 120/277 VAC | Connection Location | Back and Side | |
| Terminal Accommodation | #14 AWG - #10 AWG | Number of Gangs | 1 | |
| Throw Type | Double Throw | Amperage | 30 A | |
| Number of Poles | Single Pole | Requires Neutral Wire | Yes | |
| Indoor/Outdoor | Indoor | Mounting Type | Wall Box | |
| Wire Connection Type | Screw Terminals | Voltage | 120 VAC, 277 VAC | |
| Load Type | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon | | | |