




Pass and Seymour  
SteriGuard™ Antimicrobial Straight Blade Plug 20A, 250V, Yellow  
Part No. 14W48AM



SteriGuard Anti-Microbial Wiring Devices provide excellent protection against the growth of microbes on all surfaces. Independent testing proves the ability of these devices to inhibit the growth of Escherichia coli, Gram (-) and Staphylococcus aureus, Gram (+) providing long lasting benefits to manufacturers beyond conventional cleaning methods. Rated watertight for 1,500 psi high-pressure

## Features & Benefits

UL and CSA Listed

NSF (National Sanitation Foundation)  
Certified

Patent Pending

Anti-microbial Additives Embedded in  
polymer and inhibits Growth of Bacteria,  
Molds, Mildews and Fungi

Anti-microbial Additive Resistant to Scuffing and Cleaning

Escherichia (E.Coli): - Log reduction  
greater than 4.8, reduced surface bacteria  
by greater than 99.99%

Staphylococcus (Staph), MRSA: - Log Reduction greater than 4.3, reduces  
surface bacteria by greater than 99.97%

Salmonella : Log Reduction Greater Than  
3.6, reduces surface bacteria by Greater  
Than 99.97%

RoHS Compliant (Non-Halogenated)

Independently tested and Certified to JIS  
Z2801 standards

Resistant to High Pressure Hose-down applications

Tongue & Groove Environmental Sealing

Keyed Body and Cover for Alignment

NEMA Type 4, 4x, 6, 6P and IP67 Protection

SteriGuard: Anti-microbial Wiring Devices are ideal for a wide range of  
applications including food and beverage preparation, procession, & packaging:  
agriculture, pharmaceutical, and health care.

## Specifications

### General Info

Product Line	Pass & Seymour	Color	Yellow
Country Of Origin	United States	Application Sector	Commercial

---

Standard	CSA Listed, FSUL, UL Listed
----------	-----------------------------

---

## Dimensions

---

Product Width US	1.85 in	Product Depth US	2.62 in
------------------	---------	------------------	---------

---

## Listing Agencies / 3rd Party Agencies

---

CSA Listed	Yes
------------	-----

---

## Technical Information

---

Phase	Single	Connection	Cable
-------	--------	------------	-------

---

Number of Wires	3	Amperage	20 A
-----------------	---	----------	------

---

Number of Poles	Double Pole	Wire Size	18 - 12 AWG
-----------------	-------------	-----------	-------------

---

Voltage	250.0 V	Environmental Conditions	Moisture Resistance NEMA 3R (Flip Lid Assemblies/Back Boxes) Flammability UL94V0 (boxes & wiring device interiors) UL94V2 (cover plates) UL94HB (wiring device housings, flip lid seals) Operating Temperature -40°C (without impact) to +60°C continuous UV Resistance All exposed materials are UV stabilized
---------	---------	--------------------------	---

---