

radiant Collection Discontinued - radiant® 15A Tamper-Resistant Self-Test GFCI Outlet with Night Light Part No. 1597NTLTRBKCC4



Conducts an automatic test every three seconds, ensuring it's always ready to protect. If the device fails the test, the indicator light flashes to signal that the GFCI should be replaced. It also has our proven SafeLock Protection feature: if critical components are damaged and protection is lost, power to the receptacle is disconnected.

For detailed Tamper-Resistant receptacle information, visit our <u>Tamper-Resistant</u> <u>Receptacles page.</u>

Features & Benefits

Replaces any standard outlet with ease, in as little as 10 minutes.

Hidden sensor controls night light based on ambient light, automatically turning on when it is dark.

Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an invisible effect.

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection.

Protects against shock caused by ground-fault occurrences. Unlike breaker alternatives, GFCI outlets make it easier to fix trips with a convenient reset button on the outlet.

Features durable, high-impact resistant thermoplastic construction.

More color options available to fit any style, including finishes to match current hardware and lighting trends.

20 Amp feed-thru capacity

Specifications

General Info				
Product Line	Pass & Seymour	Replaced by Part Number	1597NTLTRBKCCD4	
Color	Black	Country Of Origin	China	
Number of Receptacles	2	Features	Combination, Nightlight	
Outlet Type	GFCI, Indoor, Residential, Self-Test, Tamper-Resistant	Warranty Type	1-Year Limited Warranty	
Dimensions				
Product Width US	1.73 in	Product Depth US	1.03 in	

Product Height US	4.2 in			
Listing Agencies / 3rd Party Agencies				
cULus Listed	Yes			
Technical Information				
Is Tamper-Resistant	Yes	Number of Gangs	1	
Amperage	15 A	Mounting Type	Вох	
Voltage	125.0 V			