

## radiant Collection radiant® 20A Duplex Self-Test GFCI Receptacles with SafeLock® Protection, Light Almond 3-Pack

Part No. 2097LA3PKCC4



GFCI receptacles from the radiant® Collection self-test automatically every three seconds to ensure reliable protection from shock due to ground fault occurrences. Meeting National Electrical Code requirements for ground fault protection, GFCI receptacles make it easier to recognize and fix trips right where they happen - no more confusion at the breaker box. 20A outlets are ideal for use with larger appliances, as well as to meet regional requirements (Chicago, Canada). GFCI protection is required by code in bathrooms, kitchens, garages, basements, outdoor areas, and for any other outlets found within six feet of a sink or water source. GFCI outlets should always be used when replacing existing GFCI outlets during renovation. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately. Spec-Grade devices are engineered to meet federal specifications for use in commercial installations.

## Features & Benefits

Protects against shock caused by ground-fault occurrences. Unlike breaker alternatives, GFCI receptacles make it easier to fix trips with a the device ever fails, the indicator light flashes to signal it should be reset button right on the device

Conducts an industry-leading automatic self-test every 3 seconds. If replaced

Equipped with proven SafeLock protection feature: if critical components are damaged and protection is lost, power to the outlet is feed-thru wiring configuration. Note: Will cut power to face and disconnected

Extends GFCI protection to "downstream" outlets when used with downstream outlets if wired incorrectly

Replaces any standard receptacle with ease, in as little as 10 minutes Features durable, high-impact resistant thermoplastic construction

More color options available to fit any style, including finishes to match current hardware and lighting trends.

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection

## Specifications

General Info					
Product Line	Pass & Seymour	Color	Light Almond		
Finish	Matte	Country Of Origin	China		
Number of Receptacles	2	Outlet Type	GFCI, Indoor, Residential, Self-Test		
Warranty Type	1-Year Limited Warranty	Туре	Outlet		
Dimensions					
Product Width US	1.73 in	Product Depth US	1.03 in		
Product Height US	4.2 in				
Listing Agencies / 3rd Party Agencies					
cULus Listed	Yes				

## Technical Information

Amperage	20 A	Number of Poles	Double Pole
Indoor/Outdoor	Indoor	NEMA Configuration Code	5-20R
Voltage	125.0 V	Environmental Conditions	95% Humidity, UL 94 V2