



GFCI receptacles from the radiant® Collection self-test automatically every three seconds to ensure reliable protection from shock due to ground fault occurrences. Meeting National Electrical Code requirements for ground fault protection, GFCI receptacles make it easier to recognize and fix trips right where they happen – no more confusion at the breaker box. 20A outlets are ideal for use with larger appliances and in commercial settings, as well as to meet regional requirements (Chicago, Canada). GFCI protection is required by code in bathrooms, kitchens, garages, basements, outdoor areas, and for any other outlets found within six feet of a sink or water source. GFCI outlets should always be used when replacing existing GFCI outlets during renovation. Spec-Grade devices are engineered to meet federal specifications for use in commercial installations.

## Features & Benefits

Alarm rated at 60 db at 10 feet	Protects children: patented shutter system helps prevent improper insertion of foreign objects meeting National Electrical Code: Tamper-Resistant requirements
Conducts an automatic test every three seconds, ensuring it's always ready to protect. If the device fails the test, the trip indicator light (red LED) flashes to signal that the GFCI should be replaced	Equipped with proven SafeLock protection feature: if critical components are damaged and protection is lost, power to the receptacle is disconnected
Feed-thru wiring configuration allows GFCI to protect downstream receptacles	Prevents line-load reversal miswire: no power to the face or downstream receptacles if wired incorrectly
Side or internal screw-pressure-plate back wire with #10-#14 AWG solid or stranded copper wire and two back wire holes per terminal	Mounting screws are shipped captive in the device and wall plate for easier installation
Dual-direction test and reset button colors match the device face	Thinner than competitors' GFCI Receptacles: leaves more room for wires in the box

## Specifications

### General Info

Product Line	Pass & Seymour	Color	White
UPC Number	785007048285	Country Of Origin	China
Application Sector	Residential/Commercial	Standard	cULus, UL Listed, FSUL

### Listing Agencies / 3rd Party Agencies

cULus Listed	Yes
--------------	-----

---

## Additional Information

---

Product Environmental Profile Yes

---

## Technical Information

---

Interrupt Rating	4 A	Frequency Rating	60 Hz
------------------	-----	------------------	-------

---

Trip Range	4 to 6 mA	Connection	Back and Side Wire
------------	-----------	------------	--------------------

---

Number of Poles	Double Pole	Voltage	125 V
-----------------	-------------	---------	-------

---

Environmental Conditions	95% Humidity, UL 94 V2
--------------------------	------------------------

---