

radiant Collection radiant® Tamper-Resistant 20A Duplex Self-Test GFCI Receptacle with SafeLock® Protection, Light Almond Part No. 2097TRLA



GFCI receptacles from the radiant® Collection self-test automatically every three seconds to ensure reliable protection from shock due to ground fault occurrences. Meeting National Electrical Code requirements for ground fault protection, GFCI receptacles make it easier to recognize and fix trips right where they happen – no more confusion at the breaker box. 20A outlets are ideal for use with larger appliances and in commercial settings, as well as to meet regional requirements (Chicago, Canada). GFCI protection is required by code in bathrooms, kitchens, garages, basements, outdoor areas, and for any other outlets found within six feet of a sink or water source. GFCI outlets should always be used when replacing existing GFCI outlets during renovation. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately. Spec-Grade devices are engineered to meet federal specifications for use in commercial installations.

Features & Benefits

5	Conducts an industry-leading automatic self-test every 3 seconds. If a the device ever fails, the indicator light flashes to signal it should be replaced.
Equipped with proven SafeLock protection feature: if critical components are damaged and protection is lost, power to the outlet is disconnected.	Extends GFCI protection to "downstream" outlets when used with s feed-thru wiring configuration. Note: Will cut power to face and downstream outlets if wired incorrectly.
Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an invisible effect.	Replaces any standard receptacle with ease, in as little as 10 minutes.
Features durable, high-impact resistant thermoplastic construction.	More color options available to fit any style, including finishes to match current hardware and lighting trends.
Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from th radiant® Collection.	e 10kA short circuit rating

20 Amp feed-thru capacity

Specifications

General Info

Product Line	Pass & Seymour	Color	Light Almond
Finish	Matte	UPC Number	785007036213
Country Of Origin	China	Number of Receptacles	2
Outlet Type	GFCI, Self-Test, Tamper- Resistant	Application Sector	Commercial, Residential
Standard	cULus, UL Listed, FSUL	Warranty Type	1-Year Limited Warranty
Туре	Outlet		

Dimensions

Product Width US1.73 inProduct Depth US1.13 inProduct Height US4.2 inListing Agencies / 3rd Party AgenciescULus ListedYesAdditional InformationProduct Environmental ProfileYesTechnical InformationNumber of Gangs1Amperage20 A-Number of PotesDouble PoteIndoor/OutdoorIndoorMounting TypeBoxEnvironmental Conditions95% Humidity, UL 94 V2				
Interview of Gangs Listing Agencies / 3rd Party Agencies Culs Listed Yes Additional Information Product Environmental Profile Yes Technical Information Number of Gangs 1 Amperage 20 A Number of Potes Double Pole Indoor/Outdoor Indoor	Product Width US	1.73 in	Product Depth US	1.13 in
cULus Listed Yes Additional Information Yes Product Environmental Profile Yes Technical Information Yes Number of Gangs 1 Amperage 20 A Number of Poles Double Pole Indoor/Outdoor Indoor	Product Height US	4.2 in		
Additional Information Product Environmental Profile Yes Technical Information Yes Number of Gangs 1 Number of Poles Double Pole Indoor/Outdoor Indoor	Listing Agencies / 3rd Party	Agencies		
Product Environmental Profile Yes Technical Information Amperage 20 A Number of Gangs 1 Amperage 20 A Number of Poles Double Pole Indoor/Outdoor Indoor	cULus Listed	Yes		
Technical Information Number of Gangs 1 Amperage 20 A Number of Poles Double Pole Indoor/Outdoor Indoor	Additional Information			
Number of Gangs 1 Amperage 20 A Number of Poles Double Pole Indoor/Outdoor Indoor	Product Environmental Profile	Yes		
Number of Poles Double Pole Indoor/Outdoor Indoor	Technical Information			
	Number of Gangs	1	Amperage	20 A
Mounting Type Box Environmental Conditions 95% Humidity, UL 94 V2	Number of Poles	Double Pole	Indoor/Outdoor	Indoor
	Mounting Type	Box	Environmental Conditions	95% Humidity, UL 94 V2