

Pass and Seymour **20A 125V Heavy Duty Spec-Grade Decorator Duplex Receptacle, Side Wire, Ivory** Part No. 26352I



Heavy-Duty Decorator Spec Grade Duplex Receptacle Back and Side Wire 20A 125V

Features & Benefits

Corrosion-resistant, plated steel strap locked into assembly to prohibit strap from bending away from body.

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.

Terminal compartments isolated from each other for positive conductor containment.

Tri-drive terminal and mounting screws.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

Heavy-duty compact design for easier installation and long lasting performance.

Impact-resistant nylon face.

All devices fit standard #26 opening wall plate.

Auto-ground clip assures positive ground.

Ivory

2

Specifications

General Info

Product Line Pass & Seymour Color Country Of Origin Mexico Number of Receptacles

Outlet Type Commercial, Indoor Application Sector Commercial

Standard UL498, cUL CSA Warranty Type 1-Year Limited Warranty

Type Outlet

Dimensions

Product Width US	1.322 in	Product Depth US	0.78 in
Product Height US	2.635 in		
Listing Agencies / 3rd Party Agencies			
cULus ListingNumber	140596	cULus Listed	Yes
Technical Information			
Dielectric Strength	Withstands 2000V minimum	Connection	Back and side wire
Number of Wires	3	Temperature Rating	-40° - 60° C
Amperage	20 A	Number of Poles	Double Pole
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor
Voltage	125.0 V	Environmental Conditions	Flammability: UL94 V2