



Wiremold  
4IN UNWIRED FLUSH STYLE ASSEMBLY SN  
Part No. 4ATSN



Designed for retrofit and new construction, Evolution Series 4" Recessed Poke-Thru devices provide convenient access to power, communications, and audio/video services recessed below floor level - providing maximum device protection. With 2 Gangs of capacity, you will be able to configure services for the needs of your space. The low-profile metal covers are available in brushed aluminum, satin brass, satin nickel, and multiple powder-coated finishes designed to match any space. Evolution Series 4" Poke-Thru devices are the perfect fit for kiosks, training rooms, classrooms, healthcare facilities or commercial buildings with open-space architecture.

## Features & Benefits

**Prewired assembly:** Save on labor with a completely assembled, prewired poke-thru with every power receptacle already installed.

**Recessed devices:** All power devices are recessed below floor level, providing maximum protection and device longevity.

**Step-on-it installation:** Quick and easy installation without the need for additional fasteners or a second installer.

**Unique cover design:** The cover opens a full 180 degrees with two unique spring-loaded slide egress doors to keep wires, connections and people safe

**Multiple finishes:** Evolution Series Poke-Thru Devices are available in multiple finishes, (BK) black, (GY) gray, (BZ) bronze, (AL) aluminum, (AA) brushed aluminum, (SB) satin brass, and (SN) satin nickel to seamlessly match your environment.

**Surface style cover assemblies:** A surface style cover is for mounting on top of the finished floor surface. The surface cover is designed to be used for carpet, tile, wood, polished concrete, or terrazzo.

**3 hour fire rating:** Evolution Series Poke-Thru Devices use an intumescent material that maintains the fire rating of any floor for up to 2 hours.

**Meets ADA accessibility guidelines:** Wide trim flange is designed to meet the ADA Accessibility Guidelines as it pertains to ADA Standard 4.5 which addresses changes in floor and ground surface levels. The poke-thru trim flanges are beveled so the slope is no greater than 1:2 ratio.

**UL Listed and UL fire classified to U.S. and Canadian safety standards:** UL Fire rated for up to 2-hour rated floors maintains the fire classification of the floor.

## Specifications

### General Info

|                 |                |                     |               |
|-----------------|----------------|---------------------|---------------|
| Product Line    | Wiremold       | Color               | Nickel        |
| UPC Number      | 786564104995   | Country Of Origin   | United States |
| Receptacle Type | Straight Blade | Number of Knockouts | 10            |

|   |            |                         |       |
|---|------------|-------------------------|-------|
| Application Sector                          | Commercial | Standard                | UL    |
| Type  | Poke-Thru  |                         |       |
| Dimensions                                  |            |                         |       |
| Cubic Capacity                              | 25 cu in   | Core Hole Size          | 4 in  |
| Additional Information                      |            |                         |       |
| Product Has Potential to Contribute to LEED | Yes        |                         |       |
| Technical Information                       |            |                         |       |
| Floor Type                                  | Concrete   | Is Tamper-Resistant     | No    |
| Fire Rating                                 | 2 hr       | Amperage                | 20 A  |
| Current Rating                              | 20 A       | NEMA Configuration Code | 5-20R |
| Voltage                                     | 125.0 V    |                         |       |