

Wiremold 6AT Prewired AV Evolution™ Poke Thru Device, Flush Style Cover, Black Part No. 6AT2PAVBK



Designed for retrofit and new construction, Evolution Series 6inch Poke-Thru devices provide convenient access to power, communications, and audio/video services recessed below floor level - providing maximum device protection. With 3-gangs of capacity that allow you to configure services for the needs of your space, services can be placed in any location within the unit. The lowprofile durable metal covers are available in six powder-coated finishes and three durable finishes, designed to match any space. The cover also features sliding doors that allow cables to neatly egress from the unit, protecting cables while reducing tripping hazards. Evolution Series 6inch Poke-Thru devices are the perfect fit for meeting and training rooms, classrooms, healthcare facilities or commercial buildings with open-space architecture.

Features & Benefits

Prewired Assembly: Save on labor with a completely assembled, prewired and A/V devices are recessed below floor level, poke-thru with every power receptacle already installed.

Step-on-it Installation. Quick and easy installation without the need for additional fasteners or a second installer.

Multiple Finishes: Evolution Series Poke-Thru Devices are available in multiple finishes: (BK) black, (GY) gray, (NK) nickel, (BS) brass, (BZ) bronze, (AA) brushed aluminum, (SB) satin brass and (SN) satin nickel to seamlessly match your environment.

A flush style cover for tile applications allows the Evolution Series Poke-Thru Devices to be adjusted to the same level as the top surface of the floor covering.

A flush style cover for tile applications allows the Evolution Series Poke-Thru Devices to be adjusted to the same level as the top surface of the floor covering.

Plug Load Control Up To 30 Feet: Tested with Pass & Seymour® Wireless RF receptacles to control plug loads up to a distance of 30 feet when the cover is closed.

Meets ADA Accessibility Guidelines. Wide trim flange is designed to meet the ADA Accessibility Guidelines as it pertains to ADA Standard 4.5 which addresses changes in floor and ground surface levels.

Fire rated for up to 2-hour rated floors maintains the fire classification of wood floors and in higher traffic applications, the floor.

Recessed Devices: All power, communications providing maximum protection and device longevity.

Unique Cover Design: The cover opens a full 180 degrees with two unique spring-loaded slide egress doors to keep wires, connections and people safe.

Ideal for High Foot Traffic Environments: Satin brass, satin nickel and brushed aluminum finishes offer a more durable, high-end look with a tougher clear powder coat.

The flush cover is designed to be used for tile or wood floors and in higher traffic applications, where a low profile is a must.

AN Ready: Plates included to accept industry standard communications and A/V devices from most manufacturers including Legrand AVIP, Extron® and more.

3 hour fire rating: Evolution Series Poke-Thru Devices use an intumescent material that maintains the fire rating of any floor for up to 3 hours, the longest of its type.

The poke-thru trim flanges are beveled so the slope is no greater than 1:2 ratio

UL Listed and UL Fire Classified to U.S. and Canadian safety standards. UL The flush cover is designed to be used for tile or where a low profile is a must.

Specifications

General Info				
Product Line	Wiremold	Color	Black	
UPC Number	786564089049	Country Of Origin	United States	
Features	Recessed	Cover Style	Flush	
Number of Knockouts	2	Application Sector	Commercial, Education, Healthcare, Hospitality	
Standard	UL Fire Classified, cULus, NEC	Warranty Type	1-Year from Installation or 2-Years from Day of Sale	
Туре	Poke-Thru			
Dimensions				
Product Width US	7.25 in	Product Weight US	9.32 lb	
Product Volume US	854.14 cu in	Product Depth US	16.25 in	
Product Height US	7.25 in	Cubic Capacity	24.5 in ³	
Core Hole Size	6 in	Knockout Size	3/4 in	
Listing Agencies / 3rd Party Agencies				
cULus ListingNumber	E2961	cULus Listed	Yes	
Trade Programs				
USMCA	Yes			
Additional Information				
RoHS Compliant	Yes			
Technical Information				
Floor Type	Carpet, Concrete, Tile, Wood	Is Pre-Wired	Yes	

Service Capacity	Dual	Fire Rating	2 hr
Number of Outlets	2		