

Pass and Seymour Double Pole, Single Phase AC Manual Motor Controller Part No. 7832MD



Double Pole, Single Phase AC Manual Motor Controller, suitable as Motor Disconnect - 10KA @ 600VAC, 30A max. Class J Fuse.

Features & Benefits

| High Horsepower rating of 20HP | Gull-wing shaped brass terminal pressure clamps |
|---|--|
| Constructed of glass-reinforced thermoplastic | UL508 and cULus Listing of individual device and assembled device within enclosure |
| Heavy-duty zinc-plated steel strap, two brass rivets secure strap to housing | External screw-pressure-plate back and side wire terminal screws unstaked for use with ring terminals |
| For covering patents, see www.legrand.us/patents. | For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here. |

Specifications

General Info

| Product Line | Pass & Seymour | Color | Aluminum |
|--------------------|------------------------|---------------------|---------------------------------------|
| Finish | Matte | UPC Number | 785007267679 |
| Country Of Origin | United States | Features | Heavy Duty Zinc Plated Steel Strap |
| Switch Type | Toggle | Number of Switches | 1 |
| Application Sector | Commercial, Industrial | Wall Plate Included | No |
| Standard | CSA Listed, UL Listed | Warranty Type | 1-Year Limited Warranty |
| Туре | Manual Controller | | |

Dimensions

| Product Width US | 4.5 in | Product Depth US | 1.8 in |
|-------------------|---------|------------------|--------|
| Product Height US | 5.75 in | | |

Listing Agencies / 3rd Party Agencies

cULus Listed

Yes

Technical Information

| Load Rating | 30 A @ 600 VAC | Operating Cycles | 50000 |
|--------------------------|----------------|------------------------|--|
| Connection Location | Back and Side | Terminal Accommodation | #14 AWG - #10 AWG |
| Number of Gangs | 1 | Throw Type | Single Throw |
| Amperage | 30 A | Number of Poles | Double Pole |
| Requires Neutral Wire | Yes | Indoor/Outdoor | Indoor |
| Mounting Type | Wall Box | Wire Connection Type | Screw Terminals |
| Voltage | 600.0 V | Load Type | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon |
| Environmental Conditions | UL94 V2 | | |
| | | | |