

## Pass and Seymour Extra Heavy Duty Hospital Grade MRI Receptacle, Back and Side Wire, 20A, 125V, White Part No. 8300WMRI

Extra Heavy-Duty Hospital Grade MRI Duplex Receptacle Back and Side-Wire 20A 125V



## Features & Benefits

Designed expressly for MRI applications.

Exclusive patented feature, circuit label on face allows permanent circuit identification.

Extra heavy-duty one-piece nickel-plated brass mounting strap with integral ground for superior structural integrity and long-term performance.

.036 inch thick, brass, triple-wipe power contacts for lasting retention.

Strap tabs wrap around and lock down on face to prevent strap from separating from face and back body.

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.

Exclusive patented feature, external screwpressure-plate back wire clamp on ground terminal for faster, easier installation.

External screw-presure-plate back wire clamps with #10 brass terminal screws for visual assurance of a good connection.

Auto-ground clip assures positive ground.

For covering patents, see www.legrand.us/patents.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

## Specifications

## General Info

Product Line	Pass & Seymour	Color	White
UPC Number	785007269178	Country Of Origin	Mexico
Application Sector	Commercial	Standard	UL498, CSA C22.2 No. 42, FEDSPEC

Dimensions					
Product Width US	1.625 in	Product Depth US	0.866 in		
Product Height US	2.75 in				
Listing Agencies / 3rd Party Agencies					
cULus ListingNumber	140596	cULus Listed	Yes		
Technical Information					
Dielectric Strength	Withstands 2000V minimum	Connection	Back and side wire		
Number of Wires	3	Temperature Rating	-40° - 60° C		
Amperage	20 A	Number of Poles	Double Pole		
Wire Size	14 - 10 AWG	Environmental Conditions	Flammability: UL94 V2		