

## radiant Collection radiant® Self-Grounding Outlet, White

Part No. 885SW



Take a step up from the standard. This duplex outlet installs easily for the basic power every home needs, while elevating your space with the sleek, clean lines of radiant® for a sophisticated look. It is also designed to automatically ground to the electrical box when installed; ideal for homes in highly-populated cities or regions where structures may not already be grounded for electrical safety. Not sure if your home's electrical wiring is grounded? Outlets with only two slots for plug prongs are not grounded. For three-prong outlets, tester devices are available to confirm proper grounding, or you can call your local electrician for an inspection. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately.

## Features & Benefits

Replaces any standard outlet with ease, in as little as 10 minutes.

Ensures grounding for electrical safety with automatic ground clip.

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection.

Features durable, high-impact resistant thermoplastic construction.

More color options available to fit any style, including finishes to match current hardware and lighting trends.

## **Specifications**

## General Info

Product Line	Pass & Seymour	Color	White
Finish	Matte	Country Of Origin	China
Number of Receptacles	2	Outlet Type	Indoor, Residential, Self- Grounding
Application Sector	Residential/Commercial	Standard	UL 498
Warranty Type	1-Year Limited Warranty	Туре	Outlet
Dimensions			
Product Width US	1.29 in	Product Depth US	1.0 in
Product Height US	4.2 in		

Listing Agencies / 3rd Party Agencies				
cULus ListingNumber	140596	cULus Listed	Yes	
Additional Information				
Product Environmental Profile	Yes			
Technical Information				
Number of Gangs	1	Amperage	15 A	
Number of Poles	Double Pole	Indoor/Outdoor	Indoor	
NEMA Configuration Code	5-15R	Mounting Type	Вох	
Voltage	125.0 V	Environmental Conditions	95% (relative humidity, non-condensing)	