



Designed for retrofit and new construction, Evolution Series 8" Recessed Poke-Thru devices provide convenient access to power, communications, and audio/video services recessed below floor level - providing maximum device protection. With 5 Gangs of capacity, you will be able to configure services for the needs of your space. The lowprofile metal covers are available in brushed aluminum, satin brass, satin nickel, and multiple powder-coated finishes designed to match any space. Evolution Series 8" Poke-Thru devices are the perfect fit for kiosks, meeting rooms, training rooms, classrooms, healthcare facilities or commercial buildings with open-space architecture. For carpet, tile, wood and laminate concrete floor coverings.

Features & Benefits

Recessed devices: All power, communications Preassembled unwired poke-thru device: Connect to conduits and install now, and A/V devices are recessed below floor level, but save configuration and plate choices for later. providing maximum protection and device longevity. Unique cover design: The cover opens a full 180 Step-on-it installation: Quick and easy installation without the need for degrees with two unique spring-loaded slide additional fasteners or a second installer. egress doors to keep wires, connections and people safe. Evolution Series Poke-Thru Devices are available in multiple finishes, (BK) black, (GY) gray, (NK) nickel, (BS) brass, (BZ) bronze, (AL) aluminum, (AA) Evolution Series Poke-Thru Devices to be brushed aluminum, (SB) satin brass, and (SN) satin nickel to seamlessly adjusted to the same level as the top surface of match your environment. the floor covering. Includes 3-gang opening: Designed to fit A/V Open system for expanded compatibility: Accepts industry standard power, devices, including wall plate style transmitters, communications and A/V devices from most manufacturers including Legrand like the Crestron DM/TX series, without any AVIP. Extron® and more. additional parts.

Plug load control up to 30 feet: Tested with Pass & Seymour® Wireless RF receptacles to control plug loads up to a distance of 30 feet when the cover is closed.

Wide trim flange is designed to meet the ADA Accessibility Guidelines as it pertains to ADA Standard 4.5 which addresses changes in floor and ground surface levels. The poke-thru trim flanges are beveled so the slope is no greater than 1:2 ratio.

The flush cover is designed to be used for tile or wood floors and in higher traffic applications, where a low profile is a must.

Specifications

General Info

A flush style cover for tile applications allows the

2 hour fire rating: Evolution Series Poke-Thru Devices use an intumescent material that maintains the fire rating of any floor for up to 2 hours.

UL Listed and UL fire classified to U.S. and Canadian safety standards: UL Fire rated for up to 2-hour rated floors maintains the fire classification of the floor.

Product Line	Wiremold	Replaced by Part Number	8ATC2AA
Color	Aluminum	UPC Number	786564089728
Country Of Origin	United States	Number of Knockouts	2
Application Sector	Commercial	Standard	cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT, cULus Listed Nonmetallic Outlet Boxes & Fittings Classified for Fire Resistance: File R8209 Guide CEYY Meets Article 300.21 300.22[C] &314 of NEC
Туре	Poke-Thru		
Dimensions			
Product Width US	9.25 in	Product Weight US	11.81 lb
Product Volume US	1390.39 cu in	Product Depth US	16.25 in
Product Height US	9.25 in	Cubic Capacity	24.5 in³
Core Hole Size	8 in		
Listing Agencies / 3rd Party	Agencies		
cULus ListingNumber	E2961	cULus Listed	Yes
Trade Programs			
USMCA	Yes		
Additional Information			
RoHS Compliant	Yes	Product Environmental Profile	e Yes
Technical Information			
Number of Outlets	0		