



6' Aluminum Plugmold Multioutlet System comprised of twelve 6 inches apart, GB

Features & Benefits

Attractive, tapered snap-together aluminum extrusions. Blend with any décor. Enables quick and easy circuit modifications or additions.

Satin anodized finish. Provides aesthetic upscale appearance and corrosion resistance.

Full range of fittings. Provides a complete wiring solution.

Factory wired in 3', 5', and 6' lengths with flush 15A, 120V specification grade receptacles. Ideal for locations requiring a high concentration of devices.

Choice of standard 6", 12" and 18" or custom receptacle spacings. Provides flexibility of outlet locations.

Choice of single circuit, alternating circuit or isolated ground receptacles. Meets any job requirement.

Customization available. All products can be modified to accommodate virtually any application.

This product meets the material restrictions of RoHS.

Specifications

General Info

| | | | |
|-----------------------|---|-------------------------|---------------|
| Product Line | Wiremold | Replaced by Part Number | AL20GB606TR |
| UPC Number | 786776044195 | Country Of Origin | United States |
| Number of Receptacles | 12 | Application Sector | Commercial |
| Standard | cULus Listed Raceway: File E4376 Guide RJBT. Multioutlet Assemblies: File E15191 Guide PVGT. Fittings: File E41751 Guide RJPR. Base & Blank Cover: Meets Article 386 of NEC. Plugmold Strips: Meets Article 380 of NEC. | Type | Plugmold |

Listing Agencies / 3rd Party Agencies

| | | | |
|------------------------|---------|-------------------------------|------------------------|
| cULus ListingNumber | E15191 | cULus Listed | Yes |
| Trade Programs | | | |
| USMCA | Yes | | |
| Additional Information | | | |
| RoHS Compliant | Yes | Product Environmental Profile | Yes |
| Technical Information | | | |
| Amperage | 15 A | Enclosure Type | Aluminum |
| Voltage | 120.0 V | Environmental Conditions | Dry interior locations |