Finish flange available in gray (GY), black (BK), ivory (VY), brushed aluminum (AL) and brass finish (BS). Aluminum and brass flanges standard with black cover. Aluminum flange also available with an aluminum colored nonmetallic cover (AA). Brass flange also available with a brass colored nonmetallic cover (AB). Includes adapters to accept eight (8) Ortronics TracJack modular jacks, four (4) Ortronics Series II modular jacks, or Wiremold Open System adapters. Modular jacks sold separately. NOTE: Assembled with scrub water gasket. For use on tile or carpet floors. AMD8 Series Poke-Thru Devices require a 4'' (102mm) diameter hole. Not designed to work with bare concrete or terrazzo. Floor covering thickness 1/8'' minimum.

Features & Benefits

Finish flange available in gray (GY), black (BK), ivory (VY), brushed aluminum (AL) and brass finish (BS).

Aluminum and brass flanges standard with black cover

Aluminum flange also available with an aluminum colored nonmetallic cover (AA)

Brass flange also available with a brass colored nonmetallic cover (AB)

Includes adapters to accept eight (8) Ortronics TracJack modular jacks, four (4) Ortronics Series II modular jacks, or Wiremold Open System adapters

NOTE: Assembled with scrub water gasket

NOTE: Assembled with scrub water gasket

For use on tile or carpet floors

AMD8 Series Poke-Thru Devices require a 4'' (102mm) diameter hole

Not designed to work with bare concrete or terrazzo

Floor covering thickness 1/8'' minimum

AMD8 Series Poke-Thru Devices require a 4'' (102mm) diameter hole

Specifications

General Info

Product Line	Wiremold	UPC Number	786564016601
Country Of Origin	Mexico	Construction	Not Assembled
Application Sector	Commercial, Education, Healthcare, Hospitality	Standard	cULus Listed, NEC
Warranty Type	1-Year from Installation or 2-Years from Day of Sale	Type	Cover

Dimensions

Product Weight US	2.319 lb

Listing Agencies / 3rd Party Agencies

cULus ListingNumber	E2961	cULus Listed	Yes

Technical Information

Floor Type	Carpet, Tile, Wood