

## Wiremold AV3ATC Assembled Poke-Thru Device

Part No. AV3ATCBS



A/V device includes one prewired 20A duplex receptacle which can be wired as a standard receptacle or isolated ground. Finish flange available in gray (GY), black (BK), ivory (VY), brushed aluminum (AL) and brass finish (BS). Aluminum and brass flanges standard with black cover. Aluminum flange also available with an aluminum colored nonmetallic cover (AA). Brass flange also available with brass colored nonmetallic cover (AB). Includes one adpater to accept Legrand AVIP or Extron Electronics MAAP mini architectural adapter plates, Wiremold Open System adapters, and Ortronics TracJack and Series II mounting adapters. Modular Jacks sold separately. NOTE: Assembled with scrub water gasket. For use on tile or carpet floors. AV3 Series Poke-Thru Devices require a 4" (102mm) diameter hole. Not designed to work with bare concrete or terrazzo. Floor covering thickness 1/8" minimum.

## Features & Benefits

A/V device includes one prewired 20A duplex receptacle which can be wired as a standard receptacle or isolated ground. Finish flange available in gray (GY), black (BK), ivory (VY), brushed aluminum (AL) and brass finish (BS). Aluminum and brass flanges standard with black cover. Aluminum flange also available with an aluminum colored nonmetallic cover (AA). Brass flange also available with brass colored nonmetallic cover (AB). Includes one adpater to accept Legrand AVIP or Extron Electronics MAAP mini architectural adapter plates, Wiremold Open System adapters, and Ortronics TracJack and Series II mounting adapters. Modular Jacks sold separately. NOTE: Assembled with scrub water gasket. For use on tile or carpet floors. AV3 Series Poke-Thru Devices require a 4" (102mm) diameter hole. Not designed to work with bare concrete or terrazzo. Floor covering thickness 1/8" minimum.

## **Specifications**

Product Line	Wiremold	UPC Number	786564015611
Country Of Origin	Mexico	Construction	Assembled
Application Sector	Commercial	Standard	cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT. cULus Listed Nonmetallic Outlet Boxes & Fittings Classified for Fire Resistance: File R8209 Guide CEYY. Meets Article 300.21 & 300.22(C) & 314 of NEC.
Туре	Poke-Thru		

Product Width US 8.25 in Product Height US 17.0 in  Listing Agencies / 3rd Party Agencies  cULus ListingNumber E2961 cULus Listed Yes  Buy American Act Compliance  NAFTA Yes  Additional Information  RoHS Conformant Yes Product Environmental Profile Yes  Technical Information								
CULus ListingNumber E2961 CULus Listed Yes  Buy American Act Compliance  NAFTA Yes  Additional Information  RoHS Conformant Yes Product Environmental Profile Yes  Technical Information	Product Width US	8.25 in	Product Height US	17.0 in				
Buy American Act Compliance  NAFTA Yes  Additional Information  RoHS Conformant Yes Product Environmental Profile Yes  Technical Information	Listing Agencies / 3rd Party Agencies							
NAFTA Yes  Additional Information  RoHS Conformant Yes Product Environmental Profile Yes  Technical Information	cULus ListingNumber	E2961	cULus Listed	Yes				
Additional Information  RoHS Conformant Yes Product Environmental Profile Yes  Technical Information	Buy American Act Compliance							
RoHS Conformant Yes Product Environmental Profile Yes  Technical Information	NAFTA	Yes						
Technical Information	Additional Information							
	RoHS Conformant	Yes	Product Environmental Profile	Yes				
	Technical Information							
Cable Entry 3/4 in Conduit Stem, .75 in Number of Outlets 2	Cable Entry	3/4 in Conduit Stem, .75 in	Number of Outlets	2				