



Pass and Seymour
Hard Use Specification Grade Switch, Gray
Part No. CSB15AC4GRY



Construction 4-Way Switch, Back and Side-Wire, 15A 120/277V.

Features & Benefits

One-piece brass alloy contact arm for reliable electrical performance.

High strength thermoplastic polycarbonate toggle resists breaking and chipping under heavy abuse.

Back body made of glass-reinforced nylon. Locking support provides resistance to face and back body separation.

Cam designed for fast make with positive break action to minimize arcing and prolong switch life.

Tri-drive terminal and mounting screws.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, [click here](#).

One-piece steel strap with integral ground is plated for corrosion resistance.

Heavy-duty toggle bumpers for smooth and quiet operation.

Available with side wire or external screw-pressure-plate back and side wire models capable of accepting #14 - #10 AWG copper or copper-clad wire.

Oversized silver alloy contacts for longer dependable switch life.

For covering patents, see www.legrand.us/patents.

Specifications

General Info

| | | | |
|-------------------|----------------|--------------------|--------------|
| Product Line | Pass & Seymour | Color | Gray |
| Finish | Matte | UPC Number | 785007126310 |
| Country Of Origin | Mexico | Application Sector | Commercial |
| Standard | UL 20, FEDSPEC | | |

Dimensions

| | | | |
|---------------------------------------|-------------------|---------------------------|----------|
| Product Width US | 1.32 in | Product Depth US | 1.073 in |
| Product Height US | 2.375 in | | |
| Listing Agencies / 3rd Party Agencies | | | |
| CSA Listed | Yes | cULus Listed | Yes |
| Technical Information | | | |
| Contact Rating | 15Amp, 120/277Vac | Closed Contact Resistance | Toggle |
| Amperage | 15 A | Number of Poles | 4-Way |
| Wire Size | #14 - #10 AWG | Wattage | 4 W |