

Wiremold Cord Ended deQuorum™ Single-Flip Up Unit

Part No. DQFP15BK

Unit includes one (1) 15A black tamper-resistant duplex receptacle. Unit comes with a 6' (1.83m) cord. Comes with a black powder coat finish.

Features & Benefits

Sleek, Attractive Design: Slimmer, lower profile integrates well with table surfaces to enhance conference rooms, meeting rooms, hotel rooms, kitchens, and offices.

Tamper-Resistant Receptacles: Meets 2011 NEC TamperResistant requirements. Receptacles feature our patented shutter system that prevents the insertion of foreign objects for safety.

New Soft Opening Cover Mechanism: Opening and closing the cover is quieter and easier with a more professional feel.

Expanded Configuration Options: Accepts full size receptacles which provides expanded custom flexibility. Consult factory for more information.

UL Spill Water Protection: Meets and exceeds UL1363 standard for relocatable power taps. Eliminates risk of shock or short circuiting due to moisture entering device.

USB Charging Capability: Duplex 3.1A USB receptacles provide charging capacity for a wide range of mobile devices.

Multiple Cover Finish Options: Durable black powder coat and brushed stainless steel finishes blend with most decors.

cULus Listed: Meets UL US and Canadian safety standards for Relocatable Power Taps (File E66421, Guide XBYS) and Mulitoutlet Assemblies (File E15191, Guide PVGT).

Specifications

Gene	eral	Info
Oelle	:I al	11110

Product Line	Wiremold	Country Of Origin	Mexico
Construction	Die Cast	Application Sector	Residential/Commercial
Standard	cULus Listed Relocatable Power Tap: File E66421 Guide XYBS, cULus Listed Multioutlet Assembly: File E15191 Guide PVGT, Meets Article 380 of NEC	Туре	Flip Up

Dimensions

Product Width US 4.75 in Product Length US 5.625 in

Listing Agencies / 3rd Party Agencies

cULus Listed Yes

Buy American Act Compliance

NAFTA	Yes		
Additional Inform	ation		
RoHS Conformant	Yes		
Technical Informa	ation		
Cable Entry	Below	Mounting Type	Recessed
Number of Outlets	2		