



Wattstopper
Discontinued - High/Low/Off PIR Outdoor Fixture Sensor, Straight Nipple, 40 ft lens, 120-480V, Bronze
Part No. FSP-221B-S-L7-BR



The FSP-2x1B sensors provide multi-level control based on motion and/or daylight contribution. They control 0-10 VDC LED drivers or dimming ballasts, as well as non-dimming ballasts and, with an FSP-Lx Lens, are rated for wet and cold locations. All control parameters are adjustable via a wireless configuration tool capable of storing and transmitting sensor profiles. The FSP-2x1B family is available in three configurations for mounting inside a fixture, to the outside of a fixture via a 1/2" knockout, or to a pole.

Features & Benefits

- Designed for LED fixtures and rated for extreme temperatures; options for box or pole mounting
- Fully adjustable high and low dimmed light levels
- Hold off setpoint with automatic calibration option for convenience and added energy savings
- Adjustable via handheld wireless configuration tool
- IP66 rated with choice of lenses for wet and outdoor locations, and mounting heights from 8' to 40'
- Adjustable time delay and cutoff delay

Specifications

General Info

Product Line	Wattstopper	UPC Number	754182940158
Country Of Origin	China		

Dimensions

Product Width US	6.024 in	Product Weight US	0.587 lb
Product Volume US	60.079 cu in	Product Depth US	3.667 in
Product Height US	2.765 in		

Additional Information

Product Environmental Profile	Yes
-------------------------------	-----

Technical Information

Sensor Type	Daylight, Occupancy	Sensor Technology	Passive Infrared (PIR), Photosensor
-------------	---------------------	-------------------	-------------------------------------