



HBP-111 with Extender

Wattstopper High/Low-Bay Extender Module for HBP-11x Series Part No. HBP-EM1

The HBP Series High Bay Passive Infrared (PIR) Occupancy Sensors provide automatic control of individual LED and fluorescent lighting fixtures in warehouses and other indoor high and low bay spaces. The lens is engineered to provide reliable coverage from a wide range of mounting heights (15ft to 40ft), and coverage can be masked for aisleway applications using a snap-on accessory (included). A hold-off daylighting feature keeps lighting off when the ambient light level is above the selected threshold. Time delay and light level settings can be adjusted via function-specific trimpots. The HBP-111 can also be adjusted remotely using a wireless configuration tool.

Features & Benefits

 Compact line voltage sensor with integral lens for 360° coverage from 15′-40′; lens covers 100′ diameter area from 40′ height; notatable snap-on aisleway masking

 Adjustable time delay and hold-off daylighting level
 HBP-111 adjustable via handheld wireless configuration tool

 120, 277, 347V, 60Hz or 230V, single phase, 50Hz operation
 cULus listed snap-in mounting hardware

Specifications

General Info

Product Line	Wattstopper	UPC Number	754182935093
Country Of Origin	China	Application Sector	Commercial
Dimensions			
Product Width US	2.0 in	Product Weight US	0.15 lb
Product Volume US	9.84 cu in	Product Depth US	5.25 in
Product Height US	0.75 in		
Technical Information			
Compatibility	HBP-111 or HBP-112		