Pass and Seymour 20A 125V Heavy Duty Spec-Grade Isolated Ground Decorator Duplex Receptacle, Back and Side Wire, White Part No. IG26362W



Isolated Ground Heavy-Duty Decorator Spec Grade Duplex Receptacle Back and Side Wire 20A 125V

Features & Benefits

IG symbol and Isolated Ground markings for easy identification and circuit delineation.	Face color coding by voltage facilitates locating and mating of proper devices.
High-impact resistant nylon face resists impacts and scrapes.	Corrosion-resistant plated steel strap.
Patented feature, external screw-pressure-plate back wire clamp on ground terminal for faster, easier installation.	Plastic barrier isolates grounding terminal from mounting strap and metal boxes.
Auto-ground clip assures positive ground.	For covering patents, see www.legrand.us/patents.
For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.	Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

Specifications

General Info

Product Line	Pass & Seymour	Color	White
Finish	Matte	UPC Number	785007842166
Country Of Origin	Mexico	Number of Receptacles	2
Application Sector	Commercial	Standard	UL498, CSA C22.2 No. 42, FEDSPEC
Туре	Outlet		
Dimensions			
Product Width US	1.322 in	Product Depth US	0.833 in

cULus ListingNumber	140596	cULus Listed	Yes	
Technical Information				
Dielectric Strength	Withstands 2000V minimum	Temperature Rating	-40° - 60° C	
Amperage	20 A	Number of Poles	Double Pole	
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor	