



20A replacement device. 6" (152mm) wire leads each side.

Features & Benefits

20A replacement device. 6" (152mm) wire leads each side.

Specifications

General Info

| | | | |
|-------------------|---------------|-----------------------|--------------|
| Product Line | Wiremold | UPC Number | 786776519921 |
| Country Of Origin | United States | Number of Receptacles | 1 |

| | | | |
|--------------------|------------|----------|---|
| Application Sector | Commercial | Standard | cULus Listed Base & Blank Cover: File E90378 Guide RJBT. Multioutlet Assemblies: File E15191 Guide PVGT. Fittings: File E90377 GuideRJPR. Base & Blank Cover & Plugmold Series w/Snapcoil Harness: Meets Article 386 of NEC. Meets Section 12-3032 of CEC. Plugmold Wired Sections: Meets Article 380 of NEC. Meets Section 12-3032 of CEC. |
|--------------------|------------|----------|---|

| | |
|------|----------|
| Type | Plugmold |
|------|----------|

Listing Agencies / 3rd Party Agencies

| | | | |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | E90377 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

Buy American Act Compliance

| | |
|-------|-----|
| NAFTA | Yes |
|-------|-----|

Additional Information

| | |
|-----------------|-----|
| RoHS Conformant | Yes |
|-----------------|-----|

Technical Information

| | | | |
|----------|---------|--------------------------|------------------------|
| Amperage | 20 A | Enclosure Type | Non-Metallic |
| Voltage | 120.0 V | Environmental Conditions | Dry interior locations |
