



The aluminum I-beam design of ITray is perfect for industrial installations with large diameter cables in long span situations, minimizing total tray width and creating a smooth transition between straight sections and fittings. A structural offset in the sidewall creates strong, mid-span splices that need fewer supports. Each splice snaps in place and stays without holding. Additionally, only four bolts are needed for each splice reducing hardware needs by 50%. These features allow Itray to be installed up to 30% faster than standard tray.

Features & Benefits

Material: Aluminum Alloy 6063

Finish: Plain

Bottom: LD: 1" wide rungSB: Flat sheet over RungSC: Solid CorrugatedVC: Vented Corrugated

Construction: Welded

Connectors: All fittings are supplied with necessary connectors and fasteners

Fitting heights (H): 4, 5, 6, 7

Specifications

General Info

| | | | |
|--------------|------------------|--------------------|---|
| Product Line | Cablofil | Finish | Hot Dipped Galvanized after Fabrication |
| UPC Number | 800388282995 | Country Of Origin | Mexico |
| Bottom Type | Ladder | Application Sector | Commercial, Industrial |
| Type | Horizontal Other | | |

Dimensions

| | | | |
|-------------------|-------------|-------------------|---------|
| Product Width US | 9.0 in | Product Weight US | 7.26 lb |
| Product Volume US | 0.469 cu ft | Product Depth US | 18.0 in |
| Product Height US | 5.0 in | | |

Trade Programs

BAA

Yes
