Llegrand[®]

Cablofil VC-4A12C-S120-36 AL 4H VENTCOR 120L 36W Part No. P300190



The aluminum I-beam design of ITray is perfect for industrial installations with large diameter cables in long span situations, minimizing total tray width and creating a smooth transition between straight sections and fittings. A structural offset in the sidewall creates strong, mid-span splices that need fewer supports. Each splice snaps in place and stays without holding, Additionally, only four bolts are needed for each splice reducing hardware needs by 50%. These features allow Itray to be installed up to 30% faster than standard tray.

Features & Benefits

| Material: Aluminum Alloy 6063-T6 | Finish: Plain |
|--|---|
| Bottom: Ldr: 1'' wide I rung SB: Flat Sheet over 12'' Rung Spacing. SC:Solid Corrugated VC: Vented Corrugated | Construction: Welded |
| Tray Design: Tray construction and markings are per the latest edition of NEMA Standards Publication VE1, CSA C22.2 No. 126. | Tray Grounding Capability: Classified as an equipment grounding conductor per NEC 392.60. |

Specifications

| General | Info |
|---------|------|
| | |

| Product Line | Cablofil | Finish | AL | |
|-----------------------------|--------------|-------------------|-----------|--|
| UPC Number | 800388060555 | Country Of Origin | Mexico | |
| Dimensions | | | | |
| Product Width US | 37.5 in | Product Weight US | 32.678 lb | |
| Product Volume US | 10.781 cu ft | Product Depth US | 120.0 in | |
| Product Height US | 4.14 in | | | |
| Buy American Act Compliance | | | | |
| ВАА | Yes | | | |