

Pass and Seymour Series 16 In-Line Connectors

Part No. PS40FBR



400A 600V, Cable Size 2/0 - 4/0, Female Cam-Type Plug, Yellow

Features & Benefits

Thermoplastic elastomer housing for outstanding impact and chemical Exceptional seal for maintaining NEMA Type 3R and resistance 4 integrity

Non-conductive retaining screw helps to insure no contact with live parts, along with providing stability to the fully assembled product

Heavy-duty hex set screws allow greater termination torque

400 A

2/0 - 4/0

Copper shim bundles wire strands to reduce "splaying."

Heavy-duty brass male and female contacts provide a superior and consistent means of conductivity

Copper wire provides quality strain relief

Number of Poles

Voltage

Single Pole

600.0 V

Specifications

Ganaral Info

General Info			
Product Line	Pass & Seymour	Color	Red
UPC Number	785007308174	Country Of Origin	Mexico
Application Sector	Commercial, Industrial	Standard	UL, cCSAus
Dimensions			
Product Length US	6.8 in		
Technical Information	n		

Amperage

Wire Size

Environmental Conditions

Operating Temperature: Maximum continuous

+75°C, minimum -40°C without impact:

Flammability UL94 V2: Enclosure: NEMA Type

3R and 4