



## Pass and Seymour

Heavy-Duty Hospital Grade Smooth Face Receptacles, Back & Side Wire, 15A, 125V, Red  
Part No. PS8200HSRED



Heavy-Duty Hospital Grade Smooth Face Duplex Receptacle Back & Side Wire 15amp 125volt Brown

### Features & Benefits

Heavy-duty, brass strap for added strength and ground conductivity.	.032 inch thick, brass, triple-wipe power contacts for lasting retention.
Strap tabs wrap around face to prevent strap from separating from face and back body.	Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.
Two drive screws anchor strap to back body and face.	Tri-drive brass terminal screws.
Internal screw-pressure-plate back and side wire capability.	Two back wire holes for more wiring flexibility.
Auto-ground clip assures positive ground.	Smooth face version features an impact-resistant nylon face for ease of cleaning and less dirt build-up.
For covering patents, see <a href="http://www.legrand.us/patents">www.legrand.us/patents</a> .	For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, <a href="#">click here</a> .

### Specifications

#### General Info

Color	Red	UPC Number	785007307177
Country Of Origin	United States	Product Line	Pass & Seymour
Application Sector	Commercial	Standard	UL498, CSA C22.2 No. 42

#### Listing Agencies / 3rd Party Agencies

cULus Listed	Yes
--------------	-----

#### Technical Information

Number of Poles	Double Pole	Voltage	125 V
Connection	Back and side wire	Dielectric Strength	Withstands 2000V minimum
Temperature Rating	Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact	Wire Size	#14 - #10

---

Number of  
Wires 3

Environmental Conditions

Flammability: UL94 V2

---