

Pass and Seymour 20A 125V Heavy Duty Hospital-Grade Duplex Receptacle, Back and Side Wire, Ivory Part No. PS8300HI

Strap tabs wrap around face to

prevent strap from separating from face and back body.

Two drive screws anchor strap to

Two back wire holes for more

For covering patents, see

www.legrand.us/patents.

back body and face.

wiring flexibility.



Heavy-Duty Hospital Grade Duplex Receptacle Back and Side Wire 20A 125V

Features & Benefits

Heavy-duty, brass strap for added strength and ground conductivity.

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.

Tri-drive brass terminal screws.

Auto-ground clip assures positive ground.

Т overload at 150% of rated current with direct current. Operating Temperature: Maximum

continuous +60°C, minimum -40°C without impact

			١
Temperature Rise: Maximum 30°C te	emperature rise at full-	rated current after 50 cycles of	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	·	,	

Specifications

General Info

Product Line	Pass & Seymour	Color	lvory
Finish	Matte	Country Of Origin	Mexico
Number of Receptacles	2	Outlet Type	Commercial, Indoor
Application Sector	Commercial	Standard	UL498, CSA C22.2 No. 42
Туре	Outlet		

Dimensions

Product Width US	1.322 in	Product Depth US	0.78 in
Product Height US	2.635 in		
Listing Agencies / 3r	d Party Agencies		
cULus Listed	Yes		
Technical Informatio	n		
Dielectric Strength	Withstands 2000V minimum	Temperature Rating	-40° - 60° C
Amperage	20 A	Number of Poles	Double Pole
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor
Voltage	125 V		