

# Pass and Seymour PlugTail® Heavy Duty Spec Grade Plug Load Controllable Receptacle, 20A, 125V, Gray Part No. PT26352SCCTGRY



These durable, dependable receptacles feature a permanently marked, differentiated solution that meets all necessary code requirements. For detailed PlugTail® information, visit our PlugTail® Headquarters.

## Features & Benefits

.032 inch thick, brass, triple-wipe power contacts for lasting retention.

Plated steel wrap strap design for maximum durability and corrosion resistance.

No exposed terminals create a finger safe application before, during, and after installation.

Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections

Permanent controlled markings on face of receptacle compliant with ASHRAE 90.1, CA Title 24, and NEC.

Auto-ground clip assures positive ground.

Half-controlled versions include welded, pre-wired lead that control top half of receptacle for split circuit applications.

For covering patents, see www.legrand.us/patents.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.

Wire Size: #12 AWG THHN

# Specifications

#### General Info

| Product Line       | Pass & Seymour | Color             | Gray  |
|--------------------|----------------|-------------------|---|
| UPC Number         | 785007496420   | Country Of Origin | Mexico                                      |
| Application Sector | Commercial     | Standard          | UL Listed, CSA Listed, cULus, FSUL, FEDSPEC |

## **Dimensions**

Product Width US 1.5 in Product Depth US 0.625 in

| Product Height US                     | 2.75 in                  |                 |        |  |  |
|---------------------------------------|--------------------------|-----------------|--------|--|--|
| Listing Agencies / 3rd Party Agencies |                          |                 |        |  |  |
| cULus Listed                          | Yes                      |                 |        |  |  |
| Technical Information                 |                          |                 |        |  |  |
| Dielectric Strength                   | Withstands 2000V minimum | Phase           | Single |  |  |
| Connection                            | PlugTail                 | Number of Wires | 3      |  |  |
| Temperature Rating                    | -40° - 60° C             | Amperage        | 20 A   |  |  |
| Number of Poles                       | Double Pole              | Wire Size       | 12 AWG |  |  |
| Environmental Conditions              | UL94 V2                  |                 |        |  |  |