

Pass and Seymour **PlugTail® 20A 125V Industrial Extra Heavy Duty Spec-Grade Duplex Receptacle, Light Almond** Part No. PT5362ALA



PlugTail® Industrial Extra Heavy-Duty Spec Grade Receptacles, 20A, 125V PlugTail® devices and connectors mean that device installation is the same regardless of skill level of the installer. The UL-Listed connectors are keyed to ensure proper wiring installation into each receptacle.

Features & Benefits

.036 inch thick, brass, triple-wipe power contacts for lasting retention.	Illuminated face indicates power to receptacle and makes it easy to identify receptacle in dark applications.
Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections.	Crimped and welded contacts.
Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing.	Large brass contacts snugly terminate on device blade terminals.
Auto-ground clip assures positive ground.	For covering patents, see www.legrand.us/patents.
For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.	Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

Specifications

General Info

Pass & Seymour	UPC Number	785007860344
Mexico	Number of Receptacles	2
Commercial, Industrial	Standard	UL 498, FEDSPEC
Outlet		
	Mexico Commercial, Industrial	Mexico Number of Receptacles Commercial, Industrial Standard

Dimensions

Product Width US	1.625 in	Product Depth US	0.86 in			
Product Height US	2.75 in					
Listing Agencies / 3rd Party Agencies						
cULus Listed	Yes					
Technical Information						
Phase	Three	Number of Wires	3			
Amperage	20 A	Number of Poles	Double Pole			
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor			