

Pass and Seymour PlugTail® Isolated Ground Spec Grade Receptacles, 15A, 125V, Orange Part No. PTIG5262



PlugTail® Isolated Ground Spec Grade Receptacles, 15A, 125A

Features & Benefits

.036 inch thick, brass, triple-wipe power contacts for lasting retention.

No exposed terminals create a finger safe application before, during, and after installation.

Crimped and welded contacts.

Large brass contacts snugly terminate on device blade terminals.

Auto-ground clip assures positive ground.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.

Plated steel wrap strap design for maximum durability and corrosion resistance.

Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections.

Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing.

Pre-stripped connector leads fasten to conductors, easier than standard pigtails.

For covering patents, see www.legrand.us/patents.

Specifications

General Info

| Product Line | Pass & Seymour | Color | Orange |
|--------------------|----------------|-------------------|-----------------|
| UPC Number | 785007307603 | Country Of Origin | Mexico |
| Application Sector | Commercial | Standard | UL 498, FEDSPEC |

Dimensions

| Product Width US | 1.5 in | Product Depth US | 0.625 in | |
|---------------------------------------|-------------|------------------|-------------|--|
| Product Height US | 2.75 in | | | |
| Listing Agencies / 3rd Party Agencies | | | | |
| cULus ListingNumber | 140596 | cULus Listed | Yes | |
| Technical Information | | | | |
| Phase | Three | Number of Wires | 3 | |
| Amperage | 15 A | Number of Poles | Double Pole | |
| Wire Size | 14 - 10 AWG | | | |