

Pass and Seymour PlugTail® Connector, Right Angle, Stranded, 6-in XHHW-2 Wire Part No. PTRA6STRX21



PlugTail® Connectors, Right Angle, Stranded, 6-inch

PlugTail® devices and connectors mean that device installation is the same regardless of skill level of the installer. The UL-Listed connectors are keyed to ensure. proper wiring installation into each receptacle. Ideal for application with low leakage current requirements. Utilizes XHHW-2 wire.

Features & Benefits

Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing.

Utilizes XHHW-2 wire which is a thermoset insulated with XLPE (cross-linked Polyethylene).

Wire temperature rated 90°C Wet/Dry.

For low leakage circuits.

Pre-stripped connector leads fasten to conductors, easier than standard pigtails.

Wire conductors Comply with NEC 517.160 for use in isolated power locations. Ideal for low leakage circuits.

Substantially higher insulation resistance than THHN wire and does not have PVC in insulation.

PlugTail™ Connector: #12 AWG, XHHW - 2, copper conductor, 6 - in leads, stripped, stranded, for use with PlugTail Receptacles only

Specifications

General Info

Product Line	Pass & Seymour	Replaced by Part Number	
Color	Gray	Country Of Origin	Mexico
Construction	Injection molded plastic	Features	Plug-In, Right Angle
Package Quantity	1	Application Sector	Commercial
Standard	RoHS, cULus	Warranty Type	1-Year

Dimensions

Product Width US	1.0 in	Product Weight US	0.06 lb
Product Height US	1.0 in	Product Length US	6.0 in
Listing Agencies / 3rd	Party Agencies		
cULus ListingNumber	E140596	cULus Listed	Yes
Additional Information			
RoHS Conformant	Yes		
Technical Information			
Wire Size	12 AWG	Indoor/Outdoor	Indoor
Connection Type	Plugtail, Wired	Environmental Conditions	0 to 95% (relative humidity, non-condensing)