



Flange available in painted gray (GY), black (BK), ivory (VY), and brushed metal finishes in aluminum (AL) and brass (BS). Aluminum and brass flanges shipped with black cover. Brass flange also available with brass colored cover assembly (AB). Aluminum flange also available with aluminum colored cover assembly (AA). Includes two (2) Ortronics TracJack adapters, two (2) Ortronics Series II adapters, and two (2) Wiremold Open System adapters. Modular jacks sold separately. NOTE: Assembled with scrub water gasket. For use on tile or carpet floors. RC9AMD Series Poke-Thru Devices require a 3 1/16'' (78mm) diameter hole. Not designed to work with bare concrete or terrazzo. Floor covering thickness 1/8'' minimum.

Features & Benefits

Flange available in painted gray (GY), black (BK), ivory (VY), and brushed metal finishes in aluminum (AL) and brass (BS).	Aluminum and brass flanges shipped with black cover
Brass flange also available with brass colored cover assembly (AB)	Aluminum flange also available with aluminum colored cover assembly (AA)
Includes two (2) Ortronics TracJack adapters, two (2) Ortronics Series II adapters, and two (2) Wiremold Open System adapters	NOTE: Assembled with scrub water gasket
NOTE: Assembled with scrub water gasket	For use on tile or carpet floors
RC9AMD Series Poke-Thru Devices require a 3 1/16'' (78mm) diameter hole	Not designed to work with bare concrete or terrazzo
Floor covering thickness 1/8'' minimum	RC9AMD Series Poke-Thru Devices require a 3 1/16'' (78mm) diameter hole

Specifications

General Info

Product Line	Wiremold	UPC Number	786564006732	
Country Of Origin	Mexico	Construction	Assembled	
Application Sector	Commercial, Education, Healthcare, Hospitality	Standard	cULus Listed, NEC	
Warranty Type	ranty Type 1-Year from Installation or 2-Years from Day of Sale		Accessory	
Dimensions				
Product Width US	7.0 in	Product Weight US	2.662 lb	

Listing Agencies / 3rd Party Agencies

cULus ListingNumbe	er E2961		сU	Lus Listed	Yes		
Additional Information							
RoHS Compliant	Yes						