

Pass and Seymour **20A 125V Fed Spec-Grade Plug Load RF Dual-Control Duplex Receptacle, Ivory** Part No. RF26352CDI



Energy savings and code compliance can be easily achieved through automatic plug load control via wireless RF communication between the Plug Load RF Signal Pack (RFP) and the Plug Load RF Receptacle.

Features & Benefits

Wireless control of plug load via RF communication and integral relay.

Product meets requirements of UL498B: Receptacles with integral switching means.

Simple, three-step binding process for wireless communication with RF Single Pack

.032 inch think, brass, triple-wipe power contacts for lasting retention.

Permanently molded face offers clear identification of controlled receptacle for end users.

Available in 'TP' series, extra 3/16 inch width and height than Standard size plates: and 'TPJ' series, extra 3/16 inch width and height than Junior-Jumbo size plates.

Binding button on face also serves as a manual override.

Corrosion-resistant plated steel strap locked into face and back body to resist pulling away from face/body assembly.

 $\ensuremath{\mathsf{LED}}$ Indicator Light on the receptacle guides binding process and indicated power to the receptacle.

Specifications

General Info

| Product Line | Pass & Seymour | Color | lvory |
|-----------------------|----------------|-------------------|----------------------|
| UPC Number | 785007039870 | Country Of Origin | China |
| Number of Receptacles | 2 | Outlet Type | Energy Saving On/Off |
| Application Sector | Commercial | Standard | FEDSPEC |
| Туре | Outlet | | |

| Dimensions | | | | |
|---------------------------|---------------|------------------|-------------|--|
| Product Width US | 1.73 in | Product Depth US | 1.25 in | |
| Product Height US | 2.68 in | | | |
| Listing Agencies / 3rd Pa | arty Agencies | | | |
| cULus Listed | Yes | | | |
| Technical Information | | | | |
| Amperage | 20 A | Number of Poles | Double Pole | |
| Indoor/Outdoor | Indoor | | | |