



Pass and Seymour
20A 125V Fed Spec-Grade Plug Load RF Dual-Control Duplex Receptacle, Light Almond
Part No. RF26352CDLA



Energy savings and code compliance can be easily achieved through automatic plug load control via wireless RF communication between the Plug Load RF Signal Pack (RFP) and the Plug Load RF Receptacle.

Features & Benefits

Wireless control of plug load via RF communication and integral relay.	Available in 'TP' series, extra 3/16 inch width and height than Standard size plates; and 'TPJ' series, extra 3/16 inch width and height than Junior-Jumbo size plates.
Product meets requirements of UL498B: Receptacles with integral switching means.	Binding button on face also serves as a manual override.
Simple, three-step binding process for wireless communication with RF Single Pack	Corrosion-resistant plated steel strap locked into face and back body to resist pulling away from face/body assembly.
.032 inch thick, brass, triple-wipe power contacts for lasting retention.	LED Indicator Light on the receptacle guides binding process and indicated power to the receptacle.
Permanently molded face offers clear identification of controlled receptacle for end users.	

Specifications

General Info

Product Line	Pass & Seymour	Color	Light Almond
UPC Number	785007040081	Country Of Origin	China
Number of Receptacles	2	Outlet Type	Energy Saving On/Off
Application Sector	Commercial	Standard	FEDSPEC
Type	Outlet		

Dimensions

Product Width US	1.73 in	Product Depth US	1.25 in
Product Height US	2.68 in		

Listing Agencies / 3rd Party Agencies

cULus Listed	Yes
--------------	-----

Technical Information

Amperage	20 A	Number of Poles	Double Pole
Indoor/Outdoor	Indoor		